

Parní lok. řady: **354.1,7**Typ jízdního odporu: **R**Minimální rychlost: **28 km/h**

Třída sklonu	Hmotnost tažených vozidel (t)													
	100	150	200	250	300	350	400	450	500	600	700	800	900	1000
I														
II							77	74	70	65	59	55	50	46
III				80	75	70	65	60	55	50	44	39	34	31
IV			78	70	64	58	53	49	44	38	32	28		
V		78	69	61	54	49	43	38	35	28				
VI	80	70	68	62	52	45	40	35	31	27				
VII	74	63	54	45	38	33	28							
VIII	69	57	47	38	32	27								
IX	63	51	41	33	27									
X	58	45	36	28										
XI	54	40	32											
XII	49	37	28											
XIII	45	33												
XIV	41	29												
XV	38													
XVI	34													

Plati od 29. 5. 1994

Parní lok. řady: **365.0**Typ jízdního odporu: **R**Minimální rychlost: **41 km/h**

Třída sklonu	Hmotnost tažených vozidel (t)													
	100	150	200	250	300	350	400	500	600	700	800	900	1000	
I											87	82	78	
II								88	80	73	67	62	57	
III							82	73	64	56	50	44		
IV					81	76	70	59	50	42				
V			87	80	70	64	58	45						
VI		89	77	70	61	54	48							
VII		80	68	62	52	45								
VIII	86	72	61	54	45									
IX	80	65	54	46										
X	74	60	48	41										
XI	68	55	43											
XII	62	50												
XIII	57	45												
XIV	52	41												
XV	48													
XVI	43													

Plati od 29. 5. 1994